

ENGINEERING CONFORMANCE CERTIFICATE

This certificate issued in accordance with RIS-1530-PLT Issue 6.

NAME OF CERTIFICATION BODY

Atkins Rail

ACCREDITATION CODE

NS

Vehicle Class/Description Road Rail Vehicle RR AP ART 17 T(H) MEWP (Type, 9A)

Vehicle Owner Story Contracting Ltd

Issue Date 7th October 2016


Expiry Date 7th October 2023

Vehicle Number: 99709 912257-1

First of Class No

Certificate Number of First of Class NS/0088/16

Authorised by:



Steve Rice
Atkins OTP and OTM Signatory

Official Stamp

Atkins Notified Body
A UKAS Accredited
Certification Body No.
6162

Reason for Issue and Scope of Work

Previous Certificate:

None, new build.

Scope of work for this certificate;

New RRV MEWP (as First of Class vehicle) with the addition of a single trailer towing capability and an instrumented pantograph, for heights and stagger recordings of **de-engergised** OHLE, based on a rail conversion of a Manitou MEWP, manufactured by Rail Products (UK) Ltd.

The MEWP is fitted with Rail Products Electronic Slew Limiting system, fitted by Rail Products EU, which meets the requirements of the remit MLD/R003 issued by Network Rail on 1st March 2013, when fitted to a ART17T MEWP, and is approved by the Network Rail Letter MLD/L054. 'Approval of MLD033, dated 24th July 2014 (see Limitations of Use item 18 and Supplementary Information items 14 & 15). Compliance with RIS-1530-PLT, Issue 6, December 2015.

Reference I/D 5150036.110

Plant Asset Manager Copy Page 1 of 5

Certificate Number. NS/0089/16

Deviations Associated with this Certificate

Reference	None.
Title	N/A

Previous Certificate Number: N/A

Approved Maintenance Instructions

ID No.	Title	Issue No.	Date
P301	ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual.	V6.4	06/10/2016
547408 EN	Manitou Instructions Manual	1	15/05/2012
P02-031-R	User Manual Instrumented Pantograph	0.4	22/06/2015

Limitations of Use

1. Vehicle is rail-conversion of a road based 4-wheel drive, 4-wheel steer mobile elevating work platform (MEWP).
2. No load carrying capability.
3. When in use, the MEWP shall have a current certificate of approval, test and/or thorough examination.
4. The MEWP shall only be used in accordance with the manufacturer's safety and operating instructions, and the safe system of work for the possession.
5. Maximum basket payload shall **NOT** exceed 400kg, (maximum three personnel + hand tools + materials).
6. It shall only operate inside possessions.
7. When working, the MEWP can be out of gauge, dependant on the slew/height settings in use.
8. For on/off tracking, a site specific plan shall be used taking account of the applicable module of Network Rail Infrastructure Plant Manual NR/PLANT/0200 and Modules P301 and P703.
9. It shall **NOT** on/off track, travel and work on live conductor-rail lines.
10. It may on/off track, travel and work on **ISOLATED** conductor-rail lines.
11. It shall **NOT** on/off track, travel, work or raise the instrumented pantograph under live OLE, except Limitation 12.
12. It is permitted to on/off track and travel under live OLE when used in conjunction with a safe system of work determined and authorised in accordance with the requirements of GE/RT8024; and provided the boom & instrumented pantograph are in the stowed and locked position for travel (the basket floor less than 1.4m above rail level - see Limitation 15). The key **MUST** be removed and given to the Machine Controller. **Minimum OLE wire height 4.165m**
13. On and Off Tracking; Detailed in the ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual V6.4. & 547408 EN Manitou Instructions Manual.
 - A RRAP or temporary crossing must be used, maximum track cant 150mm and/or gradient 1:25.
14. Alternatively to Limitation 13, a documented risk assessed procedure that is specific to the on/off tracking point may be used that is specific to the possession.
15. It is permitted to travel under live OLE subject to:
 - The basket and instrumented pantograph **MUST** be in the locked and stowed position below 1.4m, using the OLE keyswitch on Base Control; when in the On/locked position the OLE key **MUST** be removed and given to the Machine Controller.
 - There shall be no access onto the RRV except the basket.

- The earth bonds on the RRV shall have been examined for security and presence, prior to the start of work.
 - The use of the RRV under live OLE shall only be after the height of the basket floor has been checked as below 1.4m ARL, and used in conjunction with a safe system of work determined and authorised in accordance with the requirements of GE/RT8024. **OLE minimum wire height 4.165m.**
16. In recovery, speed must be limited to 3mph (5km/h) to avoid damage to the RRV.
 17. Not suitable for on ALO on LU infrastructure.
 18. ALO working is only permitted when the High Performance, Rail Products EU "Electronic Movement Limiting system" (see item 14 Supplementary Information), is fitted to this MEWP. The "ALO Limiter Selection Key switch"; to select left position or right position, **MUST** be selected **PRIOR** to commencing work (see pages 32 & 33, clause 6.2.2. "ALO Limiter Selection Key Switch" in the ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual V6.4., and the ALO Limiter Selection Key should be removed and handed to an ALO Responsible Manager. There should be a Safe System of Work (SSoW) in place to identify the required vehicle ALO limits for the planned work. To facilitate the machine working with the Adjacent Line Open to traffic refer to the system operating requirements in accordance with pages 32 & 33, clause 6.2.2. "Base station on turret" – "ALO Limiter Selection Key Switch", pages 47 & 48, clause 6.3.7., "Working with one side adjacent to open lines", in the ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual V6.4.
 - The MEWP shall only be permitted to work with adjacent lines open to traffic with the Rail Products EU "Electronic Slew Limiting system" (see Supplementary Information 14 & 15) slew limiter is switched **ON** in accordance with an accepted Safe System of Work (SSoW) incorporating a site specific survey to establish the position of the adjacent line, and to ensure the counterweight articulated boom and basket are prevented from entering the prohibited area (adjacent lines).
 - It is essential that the machine operator is trained and competent to operate, and before work takes place, carry out pre-use checks of the Rail Products EU "Electronic Slew Limiting system" in accordance with ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual V6.4., reference pages 32 & 33, part 6.2.2. "Base station on turret".
 19. Working Over the Side over the fixed axle end only with a turret rotation of up to 90° to the track, subject to the control applied by the ALO system, maximum reach 6.35m. When in Working Over the Side Mode; the MEWP telescopic arm, the whole assembly mounted on an articulated arm structure and basket can be out of gauge, dependant on the MEWP slew settings in use (see Working Over the Side in ROAD-RAIL MEWP ART 17 T-ART 17 T(H) User Manual V6.4., page 28 Part 6 Operation, and page 45, clause 6.3.5. Working Over the Side);
 - The MEWP shall only be used in accordance with the Method Statement for the possession and the safe system of work has taken account of horizontal and vertical gauge exceedance of the articulated boom and basket and at the rear side of MEWP towards the adjacent line.
 - When Working Over the Side, the MEWP system is set to move at restricted speed, (1mph), **with the telescopic arm fully retracted**, the articulated boom and basket set to work at a maximum of 90° to the track, maximum reach 6.35m, the W6a gauge of 2700mm up to a height of 1000mm is exceeded by 2150mm. (see Limitation 17).
 - A site survey shall be undertaken to assess potential damage to infrastructure equipment prior to use.
 20. When travelling in reverse, ground staff shall control movements.
 21. Except for the MEWP basket, access to any other part of the vehicle that is more than 1.4m above rail level is prohibited when under live OLE.
 22. For access/egress, the MEWP shall only operate with the basket adjacent to a cess or a line closed to all train movements, or the safe system of work takes account of adequate clearance to adjacent lines.
 23. It will **NOT** activate train operated points.
 24. Permitted speeds: Maximum travel speed – 7.5mph (12 km/h);
Maximum overside working speed – 1mph (1.6 km/h);

Maximum towing speed - 2.5mph (4 km/h).

Switches, Crossings and Raised Check Rails – 2.5mph (4 km/h).

Maximum instrumented pantograph working speed – 2.5mph (4 km/h)

25. Travelling Mode: The RRV shall **NOT** travel on track that exceeds cant 200mm and/or gradient 1:25.
26. Working Mode: The RRV shall **NOT** work on track that exceeds cant 180mm and/or gradient 1:25. Twist 1/150 over the RRV wheelbase (40mm twist).
27. The MEWP shall **NOT** work on cants above 180mm.
 - From 0mm to 120mm cant, with the telescopic arm fully extended, the maximum reach limit is 8.65m.
 - From 120mm to 180mm cant, the telescopic arm is blocked, the maximum reach is limited to 6.35m.
28. The MEWP shall **NOT** be used for any other lifting duties.
29. The vehicle is permitted to tow or propel, through couplings fitted on both ends of the machine, Rail Products UK technically matched equipment (Rail Products UK ATR 450, alu trailer).
 - Maximum weight 520.9kg including load (trailer = 70.9kg)
 - Maximum permitted number of trailers = one.
 - Trailer must be fitted with the automatic trailer breakaway warning and marker lights, using the pin plugs connected to the machine and trailer.
30. Failure recovery of the RRV MEWP shall be undertaken in accordance with the operator's manual.
31. It shall only be operated on rail when fitted with foam-filled tyres.
32. An instrumented pantograph measuring device is now fitted to the ART 17T (H) main boom and is restricted to 0° and 180° whilst in working mode. It is essential that the machine operator is trained and competent to operate the instrumented pantograph. See P02-031-R Issue 0.4, 22-06-2015 (User Manual – Instrumented Pantograph)

Supplementary Information

1. Vehicle is rail-conversion of a road based 4-wheel drive, 4-wheel steer mobile elevating work platform (MEWP).
2. RR AP ART 17 T(H) MEWP
 - Serial No. 0043066 – Fleet No. MEWP10.
 - Gross Vehicle Weight: 12,450kg.
3. The RRV is fitted with a working platform fixed on the end of a pendular arm, itself fixed to the end of a telescopic arm, the whole assembly being mounted on an articulated arm structure.
4. The lifting platform is fitted with controls in the basket. From this control station, the operator can drive and operate this machine forwards or backwards. The operator can also raise or lower the arm assembly, extend or retract the telescopic arm and turn the turret or the basket to the right or the left.
5. The basket-arm-turret assembly can rotate, non-continuously, over an angle of 360° to the left or the right with respect to the set position.
6. Notified Body (Aboma Rail) Declaration of EC TYPE examination (supplement) - Certificate No. HHC/DRS_2014_18375_IRP, Issue 4.0. Machine parameters Attached on page 2. The guidelines set out in Standards EN280:2013 have been applied herewith.
7. Notified Body (Aboma Rail) TYPE Certificate of Compliance – Certificate No. HHC/DRS_2014_18375_IRP_Issue 4. The guidelines set out in Standards EN15746-1:2010 +A1: 2011 + EN15746-2:2011 +A1:2011 have been applied herewith. – Machine based on Manitou TYPE 160AJT, Type ART 17 T(H) – dated 21-11-2014.
8. Vehicle is fitted with a Manitou Data logger.
9. Maximum allowed wind speed 45 km/h (28mph)(details from Certificates detailed in 6 & 7 above) - 12, 5 m/s (6 Beaufort).
10. Minimum Curve Radius – 80m
11. Applicable Braking Curve(s) – Road/Rail Vehicles RIS-1530-PLT Clause 5.7.3.1.
12. Applicable Gauge or Portfolio Reference: W6a as RIS-1530-PLT, Plant Gauge exceeded.


Reference I/D 5150036.110

Certificate Number. NS/0089/16

Plant Asset Manager Copy Page 4 of 5

13. Route Availability No: No change.
 14. This vehicle is fitted with a High Performance lateral movement limiting device.
 15. The vehicle is fitted with a Network Rail approved electronic slew system that has been approved by Network Rail Technical Services. The system must be configured and functioning correctly to be considered as 'reliable'.
The slew limiting system is **NOT** capable of limiting movement over both sides simultaneously. The vehicle is **NOT** permitted to work with both sides adjacent to open lines. This **MUST** be accounted for in the Safe System of Work.
-

Authorised by:

A handwritten signature in blue ink, appearing to read "Steve Rice".

Steve Rice
Atkins OTP and OTM Signatory

